according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 Jan 2021 Print date: 14 Jan 2021

Version: 1.1 Page 1/11



Applicator

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name/designation:

Applicator

Other means of identification:

UFI: U110-803C-G00J-SFC3

Article No.: KPA-250

1.2 Relevant identified uses of the substance or mixture and uses advised against Use of the substance/mixture:

Assembly tool.

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

ProGlass GmbH

Michael-Becker-Str. 2

73235 Weilheim an der Teck

GERMANY

Telephone: +49 7023 90013-0
Telefax: +49 7023 90013-23
E-mail: info@proglass.de
Website: www.proglass.de

E-mail (competent person): info@proglass.de

1.4 Emergency phone number

24h: +49 551 19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification procedure
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	Calculation
Flammable liquids (Flam. Liq. 3)	H226: Flammable liquid and vapour.	Test data
Serious eye damage/eye irritation (Eye Dam. 1)	H318: Causes serious eye damage.	Calculation

2.2 Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:







GHS02 Flame GHS05 Corrosion GHS07
Exclamation mark

Signal word: Danger

Hazard components for labelling:

Propan-1-ol; 2-Propanol

Hazard statements	for physical hazards
H226	Flammable liquid and vapour.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 Jan 2021 Print date: 14 Jan 2021

Version: 1.1 Page 2/11



Applicator

Hazard statements for health hazards		
H318	Causes serious eye damage.	
H336	May cause drowsiness or dizziness.	

Supplemental hazard information: -

Precautionary stat	Precautionary statements - Prevention		
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smo- king.		
P241	Use explosion-proof electrical equipment.		
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.		
P280	Wear protective gloves/protective clothing/eye protection/face protection.		

Precautionary statements - Response		
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P337+P313	If eye irritation persists: Get medical advice/attention.	

2.3 Other hazards

Adverse human health effects and symptoms:

Has degreasing effect on the skin. May cause skin irritation.

SECTION 3: Composition / information on ingredients

3.2 Mixtures

Additional information:

The product does not contain substances of very high concern (SVHC) \geq 0,1 %.

Ingredients:

Product identifiers	Substance name Classification according to Regulation (EC) No. 1272/2008 [CLP]	Content
CAS No.: 71-23-8 EC No.: 200-746-9 REACH No.: 01-2119486761-29	Propan-1-ol Eye Dam. 1, Flam. Liq. 2, STOT SE 3	30 - < 50 weight-%
CAS No.: 67-63-0 EC No.: 200-661-7 REACH No.: 01-2119457558-25	2-Propanol Eye Irrit. 2, Flam. Liq. 2, STOT SE 3 Danger H225-H319-H336	20 - < 30 weight-%
CAS No.: 64-17-5 EC No.: 200-578-6 REACH No.: 01-2119457610-43	Ethanol Eye Irrit. 2, Flam. Liq. 2	1 - < 10 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing. If unconscious but breathing normally, place in recovery position and seek medical advice. Do not leave affected person unattended.

Following inhalation:

Provide fresh air. Get medical advice/attention if you feel unwell.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 Jan 2021 Print date: 14 Jan 2021

Version: 1.1 Page 3/11



Applicator

In case of skin contact:

Remove contaminated, saturated clothing immediately. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

After eye contact:

In case of contact with eyes flush immediately with plenty of flowing water for 10 to 15 minutes holding eyelids apart and consult an ophthalmologist. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Following ingestion:

Rinse mouth. Do NOT induce vomiting. Get medical advice/attention if you feel unwell.

4.2 Most important symptoms and effects, both acute and delayed

Causes serious eye damage. Dizziness, Dizziness. May cause skin irritation.

4.3 Indication of any immediate medical attention and special treatment neededTreat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media:

Water spray jet, alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO2).

5.2 Special hazards arising from the substance or mixture

Flammable liquid and vapour. Vapours can form explosive mixtures with air. Reignition possible over considerable distance. Heating causes rise in pressure with risk of bursting. Move undamaged containers from immediate hazard area if it can be done safely. Use water spray to keep fire-exposed containers cool. Heat: Thermal decomposition.

Hazardous combustion products:

In case of fire may be liberated: carbon monoxide (CO), carbon dioxide (CO2), gases/vapours, toxic.

5.3 Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4 Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

Personal precautions:

Provide adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with eyes and skin. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Remove persons to safety.

Protective equipment:

Wear protective gloves/protective clothing/eye protection/face protection.

6.1.2 For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8

6.2 Environmental precautions

Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up:

Water with tenside additive

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 Jan 2021 Print date: 14 Jan 2021

Version: 1.1 Page 4/11



Applicator

6.4 Reference to other sections

Safe handling: see section 7.

Personal protection equipment: see section 8.

Disposal: see section 13.

6.5 Additional information

Use appropriate container to avoid environmental contamination.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Advices on safe handling:

Do not breathe gas/fumes/vapour/spray. Use only in well-ventilated areas. Avoid contact with skin, eyes and clothes. Repeated exposure may cause skin dryness or cracking. Wear personal protection equipment (refer to section 8).

Fire prevent measures:

Flammable liquid and vapour. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Provide earthing of containers, equipment, pumps and ventilation facilities. Use explosion-proof electrical equipment. Vapours can form explosive mixtures with air. The vapour of the product is heavier than air and may accumulate below ground level, in pits, channels and basements in higher concentration. Beware of reignition. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches.

Environmental precautions:

Discharge into the environment must be avoided.

Advices on general occupational hygiene

Wash hands before breaks and after work. When using do not eat, drink or smoke. Take off contaminated clothing and wash it before reuse. Apply skin care products after work. Draw up and observe skin protection programme.

7.2 Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

Requirements for storage rooms and vessels:

Floors should be impervious, resistant to liquids and easy to clean. Keep/Store only in original container.

Hints on storage assembly:

Keep away from combustible material. Do not store together with: oxidizing agent. Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions:

Protect from sunlight.

7.3 Specific end use(s)

Recommendation:

Assembly tool.

Observe instructions for use.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 Jan 2021 Print date: 14 Jan 2021

Version: 1.1 Page 5/11



Applicator

SECTION 8: Exposure controls / Personal protection

8.1 Control parameters

8.1.1 Occupational exposure limit values

Limit value type (country)	Substance name	 Long-term occupational exposure limit value Short-term occupational exposure limit value Instantaneous value Monitoring and observation processes Remark
WEL (GB)	Propan-1-ol CAS No.: 71-23-8	① 200 ppm (500 mg/m³) ② 250 ppm (625 mg/m³) ⑤ (may be absorbed through the skin)
WEL (GB)	2-Propanol CAS No.: 67-63-0	① 400 ppm (999 mg/m³) ② 500 ppm (1,250 mg/m³)
WEL (GB)	Ethanol CAS No.: 64-17-5	① 1,000 ppm (1,920 mg/m³)

8.1.2 Biological limit values

No data available.

8.1.3 DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type	
		② Exposure route	
Propan-1-ol	268 mg/m ³	① DNEL worker	
CAS No.: 71-23-8		② Long-term – inhalation, systemic effects	
Propan-1-ol	80 mg/m³	① DNEL consumer	
CAS No.: 71-23-8		② Long-term – inhalation, systemic effects	
Propan-1-ol	136 mg/kg	① DNEL worker	
CAS No.: 71-23-8		② Long-term - dermal, systemic effects	
Propan-1-ol	81 mg/kg	① DNEL consumer	
CAS No.: 71-23-8		② Long-term - dermal, systemic effects	
Propan-1-ol	61 mg/kg	① DNEL consumer	
CAS No.: 71-23-8		② Long-term - oral, systemic effects	
2-Propanol	500 mg/m ³	① DNEL worker	
CAS No.: 67-63-0		② Long-term – inhalation, systemic effects	
2-Propanol	89 mg/m³	① DNEL consumer	
CAS No.: 67-63-0		② Long-term – inhalation, systemic effects	
2-Propanol	888 mg/kg	① DNEL worker	
CAS No.: 67-63-0	bw/day	② Long-term - dermal, systemic effects	
2-Propanol	319 mg/kg	① DNEL consumer	
CAS No.: 67-63-0		② Long-term - dermal, systemic effects	
2-Propanol	26 mg/kg	① DNEL consumer	
CAS No.: 67-63-0		② Long-term - oral, systemic effects	
Ethanol	600 mg/m ³	① DNEL worker	
CAS No.: 64-17-5		② Long-term – inhalation, systemic effects	
Ethanol	106 mg/m ³	① DNEL worker	
CAS No.: 64-17-5		② Long-term – inhalation, systemic effects	
Ethanol	114 mg/m ³	① DNEL consumer	
CAS No.: 64-17-5		② Long-term – inhalation, systemic effects	

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 Jan 2021 Print date: 14 Jan 2021

Version: 1.1 Page 6/11



Applicator

Substance name	DNEL value	① DNEL type ② Exposure route
Ethanol CAS No.: 64-17-5	1,900 mg/m ³	① DNEL worker ② Acute - inhalation, local effects
Ethanol CAS No.: 64-17-5	950 mg/m ³	① DNEL worker ② Acute - inhalation, local effects
Ethanol CAS No.: 64-17-5	1,161 mg/kg bw/day	DNEL worker Long-term - dermal, systemic effects
Ethanol CAS No.: 64-17-5	412 mg/kg bw/day	① DNEL worker ② Long-term - dermal, systemic effects
Ethanol CAS No.: 64-17-5	206 mg/kg	DNEL consumer Long-term - dermal, systemic effects
Ethanol CAS No.: 64-17-5	31 mg/kg bw/day	DNEL worker Long-term - oral, systemic effects
Ethanol CAS No.: 64-17-5	87 mg/kg	① DNEL consumer ② Acute – oral, systemic effects

Substance name	PNEC value	① PNEC type
Propan-1-ol CAS No.: 71-23-8	10 mg/L	① PNEC aquatic, freshwater
Propan-1-ol CAS No.: 71-23-8	22.8 mg/kg	① PNEC sediment, freshwater
Propan-1-ol CAS No.: 71-23-8	2.2 mg/kg	① PNEC soil, freshwater
2-Propanol CAS No.: 67-63-0	140.9 mg/L	① PNEC aquatic, freshwater
2-Propanol CAS No.: 67-63-0	140.9 mg/L	① PNEC aquatic, marine water
2-Propanol CAS No.: 67-63-0	2,251 mg/L	① PNEC sewage treatment plant
2-Propanol CAS No.: 67-63-0	552 mg/kg	① PNEC sediment, freshwater
2-Propanol CAS No.: 67-63-0	160 mg/kg	① PNEC secondary poisoning
2-Propanol CAS No.: 67-63-0	140.9 mg/L	① PNEC aquatic, intermittent release
2-Propanol CAS No.: 67-63-0	28 mg/kg	① PNEC soil, freshwater
Ethanol CAS No.: 64-17-5	0.96 mg/L	① PNEC aquatic, freshwater
Ethanol CAS No.: 64-17-5	0.79 mg/L	① PNEC aquatic, marine water
Ethanol CAS No.: 64-17-5	3.6 mg/kg	① PNEC sediment, freshwater
Ethanol CAS No.: 64-17-5	287.7 mg/kg	① PNEC sediment, marine water
Ethanol CAS No.: 64-17-5	0.63 mg/kg	① PNEC soil, freshwater

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Technical measures and the application of suitable work processes have priority over personal protection equipment. Generation/formation of aerosols: Devices with local exhaust / Technical ventilation of workplace

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 Jan 2021 Print date: 14 Jan 2021

Version: 1.1 Page 7/11



Applicator

8.2.2 Personal protection equipment







Eye/face protection:

Eye glasses with side protection (EN 166).

Skin protection:

Tested protective gloves must be worn (EN ISO 374).

Suitable material: IIR (Butyl rubber)

Thickness of the glove material: ≥ 0,5 mm

Breakthrough time:: ≤ 480 min

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. The exact breakthrough time must be requested from the protective glove manufacturer and must be observed. Check leak tightness/ impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well.

Respiratory protection:

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Suitable respiratory protection apparatus: Filter type A

Other protection measures:

Wear anti-static footwear and clothing

8.2.3 Environmental exposure controls

No data available.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state: liquid Colour: colourless

Odour: after Alcohol

Safety relevant basic data

Parameter		at	Method	Remark
рН	6	20 °C		
Melting point	not determined			
Freezing point	not determined			
Initial boiling point and boiling range	≥ 82 °C			(Isopropanol)
Decomposition temperature	not determined			
Flash point	25 °C		DIN 51755 part- 1	
Evaporation rate	not determined			
Auto-ignition temperature	not determined			
Upper/lower flammability or explosive limits	2 %			
Vapour pressure	40 hPa	20 °C		
Vapour density	not determined			
Density	0.86 g/ml	20 °C		
Bulk density	not applicable			
Water solubility	completely mis- cible			
Partition coefficient: n-octanol/ water	not determined			
Dynamic viscosity	not determined			
Kinematic viscosity				
VOC content	74.73 weight-%			

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 Jan 2021 Print date: 14 Jan 2021

Version: 1.1 Page 8/11



Applicator

9.2 Other information

No data available.

SECTION 10: Stability and reactivity

10.1 Reactivity

Flammable liquid and vapour.

10.2 Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3 Possibility of hazardous reactions

Possibility of hazardous reactions/Exothermic reaction with: Oxidizing agent; Acidn, Alkali (lye), Light metals (Formation of: Hydrogen). Vapours can form explosive mixtures with air.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

10.5 Incompatible materials

oxidizing agent, strong; Acids, Alkali (lye)

10.6 Hazardous decomposition products

No known hazardous decomposition products.

In case of fire may be liberated: carbon monoxide (CO), carbon dioxide (CO₂), gases/vapours, toxic.

Further information

No data available.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met. Has degreasing effect on the skin. May cause skin irritation.

Serious eye damage/irritation:

Causes serious eye damage.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Additional information:

No data available.

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 Jan 2021 Print date: 14 Jan 2021

Version: 1.1 Page 9/11



Applicator

SECTION 12: Ecological information

12.1 Toxicity

Aquatic toxicity:

Based on available data, the classification criteria are not met.

Assessment/classification:

The substance/mixture does not fullfill the criteria of the acute aquatic toxicity according to Regulation (EC) No 1272/2008 [CLP], Annex I.

12.2 Persistence and degradability

Additional information:

On the basis of existing data about the elimination/degradation and bioaccumulation potential longer term damage to the environment is unlikely.

12.3 Bioaccumulative potential

Accumulation / Evaluation:

No indication of bioaccumulation potential.

12.4 Mobility in soil

No data available.

12.5 Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6 Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment options

Appropriate disposal / Product:

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal.

Appropriate disposal / Package:

Dispose of waste according to applicable legislation. Completely emptied packages can be recycled.

Other disposal recommendations:

The allocation of waste code numbers / waste names must be carried out in accordance with the European Waste Catalogue (EWC). Collect in closed and suitable containers for disposal. Do not allow to enter into surface water or drains.

13.2 Additional information

Waste for disposal is to be classified and labelled.

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI-/IATA-DGR)	
14.1 UN-No.				
1987	1987	1987	1987	
14.2 UN proper shipping name				
ALCOHOLS, N.O.S. (n-PROPANOL, ISOPROPANOL)	ALCOHOLS, N.O.S. (n-PROPANOL, ISOPROPANOL)	ALCOHOLS, N.O.S. (n-PROPANOL, ISOPROPANOL)	ALCOHOLS, N.O.S. (n-PROPANOL, ISOPROPANOL)	

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 Jan 2021 Print date: 14 Jan 2021

Version: 1.1 Page 10/11



Applicator

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI-/IATA-DGR)
14.3 Transport ha	azard class(es)		
	•	*	*
3	3	3	3
14.4 Packing grou	nb		
III	III	III	III
14.5 Environment	tal hazards		
No	No	No	No
14.6 Special prec	autions for user		
No data available.			

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

not determined

Additional information:

Transport as "Limited Quantity" according to chapter 3.4 ADR/RID

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1 EU legislation

Other EU regulations:

Directive 98/24/EC of 7 April 1998 on the protection of the health and safety of workers from the risks related to chemical agents at work Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

15.1.2 National regulations

No data available.

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

16.1 Indication of changes

Changes executed in version 1.1:

Section 1: UFI General revision

16.2 Abbreviations and acronyms

See overview table at www.euphrac.eu

16.3 Key literature references and sources for data

European Chemicals Agency (ECHA): http://www.echa.europa.eu

ECHA, C&L Inventory: http://echa.europa.eu/information-on-chemicals/cl-inventory-database ECHA, Registered substances: http://echa.europa.eu/information-on-chemicals/registered-substances GESTIS (Gefahrstoffinformationssystem der DGUV): http://www.dguv.de/ifa/GESTIS/index.jsp Hörath Gefährliche Stoffe und Gemische, 8. Auflage, Dr. Angela Schulz

Safety data sheets of the manufacturers

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 7 Jan 2021 Print date: 14 Jan 2021

Version: 1.1 Page 11/11



Applicator

16.4 Classification for mixtures and used evaluation method according to regulation (EC) No. 1272/2008 [CLP]

Classification according to Regulation (EC) No. 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification procedure
STOT-single exposure (STOT SE 3)	H336: May cause drowsiness or dizziness.	Calculation
Flammable liquids (Flam. Liq. 3)	H226: Flammable liquid and vapour.	Test data
Serious eye damage/eye irritation (Eye Dam. 1)	H318: Causes serious eye damage.	Calculation

16.5 Relevant H- and EUH-phrases

Hazard statements		
H225	Highly flammable liquid and vapour.	
H318	Causes serious eye damage.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	

16.6 Training advice

No data available.

16.7 Additional information

The information in this safety data sheet has been established to our best knowledge and was upto-date at time of revision. The information is intended to give you advice about the safe handling of the product for storage, processing, transport and disposal. It does not represent a guarantee for the properties of the product described in terms of the legal warranty regulations.